

Module characteristics

.Power full and stable: produced according to **UFLEX**'s strict quality requirements .Module efficiency of up to 9.52 %
 .5 years product and workmanship warranty .10 years performance warranty on 90%, 25 years on 80% of initial output

.TUV certified quality
 .Robust 22mm cavity frame (screwless)
 .Maximum surface load to 5400 Pa*
 .Delivery of positive tolerance modules only
 .Completely recyclable

Electrical data - typical (STC*)

Capacity rating WP	Pmax	10
Power Tolerance in	%	+/- 3
Module efficiency	%	9.52
Rated voltage in V	Vpm	17.7
Rated current in A	Ipm	0.57
Open circuit voltage in V	Voc	21.5
Short circuit current in A	Isc	0.65

Mechanical specification

Solar cells	36 pcs polycrystalline Silicon Cells
Cell encapsulation	Highly transparent EVA (Ethylene-Vinyl-Acetate)
Backside	Highly reflective UV protected backsheet
Frame	Anodised aluminium cavity frame (screwless)
Front glass	Low Iron tempered Solar glass

Temperature coefficients (TC)

Tc of open circuit voltage	Voc	-0.35% /°C
Tc of short circuit current	Isc	0.06 % /°C
Tc of power	Pmax	-0.45 % /°C

Permissible operating conditions

Temperature range	-40°C to + 85°C
Maximum system voltage	600 V DC
Maximum surface load	Tested up to 5400 Pa according to IEC 61215*
Hail resistance	Maximum diameter of 25 mm with velocity 24 m/s*

Mechanical specification

Dimentions (L x W x H)	300mm X 350mm X 22 mm(Optional 15mm)
Weight	1.2 kgs
Junction box	IP 65 certified 2-rail. 1 diode junction box
Cable	Optional
Remark	2 mm thickness of the junction box over the frame thickness


Guarantees and certifications

Product warranty	5 years
Performance guarantee	Guaranteed Output power 90% for 10 years and 80% for 25 years
Approvals and certificates	TUV : IEC 61215, IEC 61730, IEC 61701 (Salt mist test)

Electrical safety Class II

*STC (Standard test conditions): Irradiation 1000 W/m², Temperature 25°C, AM 1.5 NOCT: 46 ± 2°C

Drawing measurement in mm



APPLICATIONS



"Manufactured in: ISO 9001: 2008 certified facility in India"

UFLEX S.r.l.

Via Milite Ignoto 8A
 16012 Busalla (GE) - Italy
 T +39 010 9620228 / 203 / 230
 F +39 9629333
 ut@ultraflexgroup.it
 www.ultraflexgroup.it

Packing information

Module Quantity/Outer Box: 10, Outer Box Size : 330 X 330 X 380 mm

Due to constant product modifications, **UFLEX** reserves the right to amend the above specifications without prior notice.

* - Terms and conditions apply.